



**Required Fees (Continued)**

PLUMBING.....	\$ _____
WATER MAIN TAP.....	\$ _____
PLUMBING EXTERIOR.....	\$ _____
STORM SEWER TAP.....	\$ _____
WATER METER .....	\$ _____
STREET OPENING DEPOSIT REGUNDABLE.....	\$ _____
SUBTOTAL CIVIL ENGINEERING .....	\$ _____
SUBTOTAL WATER FUND .....	\$ _____
SUBTOTAL BUILDING FEES .....	\$ _____
SUBTOTAL DEPOSITS REFUNDABLE .....	\$ _____

**J.U.L.I.E.**

Arrangements shall be made for adequate protection against interference with underground utilities by calling J.U.L.I.E. 1-800-892-0123 or 811 and MORTON GROVE PUBLIC WORKS 847/ 470-5235 AT LEAST 48 HOURS BEFORE EXCAVATING OR DIGGING.

**PARKWAY SPRINKLERS**

If it is necessary for the Village or other public utility to make any repairs in the Village owned parkway, and should our Sprinkler system be damaged, we assume all costs and responsibility for any and all repairs, replacements, etc to the sprinkler system.

**Property owners:** \_\_\_\_\_ **Date:** \_\_\_\_\_

-----  
**The undersigned hereby makes application for a permit to erect a building / structure, etc. In the Village Of Morton Grove and in accordance with the ordinances of the Village of Morton Grove and in accordance with the plans and specifications herewith submitted and filed in consideration of the issuance of this permit, and other good and valuable considerations the receipt of which is hereby acknowledged, we/I do hereby agree and covenant to forever hold harmless the Village of Morton Grove, Its agents and employees, and to save them from all costs, claims, suits, demands, and actions arising from or through or because of or in any way connected with any work performed or being done in the excavation, construction, building, or finishing of the premises for which this permit is issued.**  
-----

**Date:** \_\_\_ / \_\_\_ / \_\_\_ **Contractor:** \_\_\_\_\_

**Date:** \_\_\_ / \_\_\_ / \_\_\_ **Property Owner:** \_\_\_\_\_

**Date:** \_\_\_ / \_\_\_ / \_\_\_ **Building Official:** \_\_\_\_\_

# Village of Morton Grove

## SEWER REPAIR AND FLOOD CONTROL INSTALLATION REQUIREMENTS FOR THE VILLAGE OF MORTON GROVE

1. Sewer repairs made within five feet of the foundation wall must be performed by a licensed plumbing contractor.
2. Sewer repairs made within five feet of the foundation wall must be installed with Cast iron or Schedule 40 PVC pipe.
3. Sewer repairs or flood control systems installed within ten feet of the water Service must be installed with Cast Iron or Schedule 40 PVC.
4. Sewer repairs made within ten feet of a water service shall be made with Schedule 40 PVC or Cast Iron.
5. For installations with ten feet or more separation between the sewer and water, SDR 26 may be used to within five feet of the foundation.

Questions concerning these installations can be referred to the Village of Morton Grove plumbing inspector by calling 847-470-5214.

### **10-3-4: OVERHEAD PLUMBING REGULATIONS:**

10-3-4-D: Storm Water Discharge: Downspouts and storm water drains shall not be connected to the sanitary sewer but shall be discharged on splash blocks to run into a dry well located not less than ten feet (10') from any building wall.